



# MOTORIZED FOLDING MACHINE EVO Center

### The new generation EVO Center The best solution to achieve maximum performance

A Schröder EVO Center is your industrial solution to achieve large-volume as well as flexible series production with utmos repeat accuracy.



Based on our technology, our hardware and our software we have developed a folding machine that is able to process sheet metal in almost fully-automatic operation. The central core of the Schröder EVO Center is based on our long-term experience we have gained with our modern folding machines of the Evolution series. Thanks to an intelligent set-up technique, the Schröder EVO Center can be used efficiently for serial production as well as for order-related production with fast changing small batches. A fully automatic tool changer equips the clamping beam quickly and accurately with tools. The tool changer and the handling system are driven by our intelligent software control POS 3000.

Standard equipment			
Software control	<ul> <li>POS 3000 3-D graphic control with 22" TFT touch-screen colour display movable via guide rail</li> <li>Radius function</li> <li>Remote maintenance</li> <li>External programming (PC-Version 1st licence)</li> </ul>		
Clamping beam	<ul> <li>Z-axis drive max. axis speed: 120 mm/sec</li> <li>Geometry clamping beam: 180°</li> <li>Clamping beam stroke: 850 mm</li> <li>Tool clamping, hydraulic (WZS 6000)</li> <li>Fully automatic tool changer for clamping beam tools for max. tool height 400 mm, 2 asynchronously movable tool changers with one gripper unit each</li> </ul>		
Folding beam	<ul> <li>Up'n Down folding beam, program-controlled</li> <li>Tool clamping, pneumatic (WZS 7000)</li> <li>Adjustment, motorized: 200 mm</li> <li>Central crowning device, motorized</li> <li>Motorized center point adjustment, converter-controlled drive</li> </ul>		
Gauge system	<ul> <li>Gauge table 1700 mm as U-shape, divided support plates with steel balls</li> <li>Lateral angle gauge right and left side 1500 mm (outside)</li> <li>Suction plates in gauge table, controlled via POS 3000</li> <li>2 pneumatic pop-up square arms assembled aisle side, program-controlled</li> <li>Gauge axis in front</li> </ul>		
Drives	<ul> <li>Servoconverter-controlled drives for clamping beam, folding beam, B-Axis, D-Axis and back gauge</li> </ul>		
Work safety	<ul> <li>Protection via light curtain controlled by safety-PLC for operation from the rear</li> <li>Safety at the front via double-leaf sliding door</li> </ul>		
Others	<ul> <li>Air conditioner on both switch cabinets</li> <li>Foot switch with two pedals incl. protection cover</li> <li>Anchor plates incl. dowels</li> <li>Standard machine without tools</li> </ul>		

Special equipment			
Back gauge system	<ul> <li>Side table left or right, support table closed with ball rollers. Technical data, see page 11</li> <li>Pneumatically lowerable gauge fingers (2 sectors 850/1700 mm)</li> <li>Various back gauge extensions right and/or left with pneumatically lowerable gauge fingers (balls in table), combinable with side table</li> </ul>		
Others	<ul> <li>Voltage transformer 18 kVA</li> <li>Tools see page 6-7</li> <li>Options to control see page 8-9</li> </ul>		

## Fully automatic tool changer

Precise and extremely fast: The fully automatic tool changer allows you to reduce preparation times for small series effectively, reduces equipping errors, and increases output at the same time.



Two rotating units with one gripper arm each remove the tools from the magazine.



Additional operator terminal on the rear – free-standing column turnable and height-adjustable. Safety for operation from the rear: light curtain controlled by safety-PLC.

#### Quick and safe tool set-up

2

The EVO Center may be equipped with a fully automatic tool changer. In just a few seconds, the clamping beam (and optionally the folding beam) can be equipped with tools. Two rotating units operated via highly precise linear drives remove the tools from the magazine using one gripper arm each and then position them in the tool clamping device or disassemble the current tools.

All information about products, upcoming orders, and the required tools are received by the tool changer via Schröder's POS 3000 software control.

The fully automatic tool changer of the EVO Center adresses the central challenges of your production processes:

Reducing set-up times

Minimize downtimes, shorten processing times, increase output and efficiency.

Avoid errors

The wrong tool is a frequent cause of errors in sheet metal forming. Errors can be avoided with automatic tool equipping. Quality increases, waste and costs are reuced.

Produce more flexibly and cost-effectively The production lot sizes are decreasing - with automatic tool chaning, even small lot sizes and single pieces are no longer to be feared as lost efficiency and source of errors. Your company can make cheaper offers and generate additional orders.

## Automation, robotics and sensor technology

The EVO Center can be extended at any time to a fully automatic bending center. In order to achieve efficient production processes, we count on intelligent automation solutions.



Customized solution: Roller table for unloading the final product

Safety at the front via double-leaf sliding door

Customized solution: Possibility to use robotic systems: the sheet gets picked up via suction cups

Fully-automated feed-in and feed-out in Schröder bending centers are based on industrial roboters of leading manufacturers, e.g. KUKA.

Tables, delivery systems, gauge techniques and highly fl exible manipulators bring the work pieces in the right position. Here, the work pieces are measured exactly by new camera systems – this guarantees top values for precision and repeatability for each bend.

Lightbarriers, movement- and touch sensors ensure safe operations of the bending center.

Upon request we offer you fully-automatic feed-in and feed-out solutions in our EVO Center: In order to automate production processes we count on proven suppliers of reliable components. Customized solutions may be:

- Adjustment on clamping-, bottom-, or folding beam
- Special gauge solutions incl. software
- Special dimension
- Special tools
- Robotic solutions for feed-in and feed-out

Your individual sheet metal solutions will be developed and produced completely in-house. Feel free to contact us and we will work out together a customized solution for your requirements.

## Tools

With the EVO Center we offer you the right tools for your special requirements. Thanks to the fully automatic tool changer and a great choice of highly precise and long-lasting tools you will achieve accurate results from the first bending product.



Optional a folding beam tool changer is available.

Picture above: Different tools for all requirements Picture below: Fully automatic clamping beam tool changer for maximum clamping beam tool height 400 mm

As a flexible platform the EVO Center is able to adapt to production-specific requirements using specific tools. When it comes to the bending process the right tool is essential – with the SPB Evolution UD we can push all limits. For every product we can offer you the suitable tool for the clamping-, bottom- and the folding beam. Should you require a particular geometry, just let us know. We will work out a customized solution for you.

#### Flexibility thanks to automatic tool changing

Thanks to intelligent set-up techniques the EVO-CENTER can be used efficiently not only for serial production but also for order-related manufacturing with fast changing small batches and single pieces.

The fully automatic tool changer of the EVO Center equips the clamping beam quickly and precisely with tools for a maximum clamping beam tool height of 400 mm. The automatic tool changer consists of two tool grippers that move asynchronously, take tools from the magazine, position them in the clamping beam and reposition the currently used tools respectively.

Optionally, there is an automatic tool changer for folding beam tools available. The tools are clamped pneumatically here.

#### Special tools

Tool options					
Bottom beam tools WZS* 10400 surface hardened ca. 1100 N/mm <sup>2</sup> (nitrated)	Bottom beam blade one-piece, directly screwed - without finger grooves (min. gauge 130 mm) - with finger grooves				
Folding beam tools WZS 7000 surface hardened ca. 1100 N/mm <sup>2</sup> (nitrated)	Folding blade segmented $(101/81 \times 65 \text{ mm})$ No. 1 - L = 2x $(25/30/35/40/45/50) = 450 \text{ mm}$ No. 2 - L = 200 mm (number according to work. length) Folding blade width: 10/15/20/25/30/35/40/50  mm				
Tool changer Folding beam WZS 7100	Tool changer folding beam Additional option automatic tool changer for fol- ding beam tools with pneumtic tool clamping incl. one folding beam tool set.				
Clamping beam tools WZS 6000 surface-hardened ca. 1100 N/mm <sup>2</sup> (nitrated)	Goat's foot segment "C", 30°, (from radius 1.0 mm) clearance 70 mm, clamping range 104 mm No. 1 - L = 2x ( $30/35/40/45/50/55/60$ ) = 630 mm No. 2 - L = 80 mm (number according to working length) H = 330 mm or H = 400 mm				
Corner parts	<ul> <li>1 pair corner parts, L= 2x 110 mm = 220 mm (suitable for goat's foot set)</li> <li>additional pair of hinged corner parts for tool heights from 250 mm</li> <li>Clamping beam drive for active driven corner parts (free space of total clamping beam tooling is reduced by 31mm)</li> <li>Additional pair of hinged corner parts – active drive for tool heights from 250 mm (free space of toal clamping beam tooling is reduced by 31 mm)</li> </ul>				

\* WZS = Tool system



A human-machine interface the way it should be: The EVO Center from Schröder receives its instructions via a 22" touch display. Above: The control software becomes a convenient product catalog. Below: Not only the work piece is displayed, the tools are also shown – in this case, in the mounting plan.

## POS 3000 3D graphic control:

## Interactive sheet design

With the POS 3000 3D graphic control, our sheet metal working specialists are setting new standards in the control of industrial sheet metal processing.

The new, high-end POS 3000 control and the folding machine EVO Center from Schröder are a perfect match, including control over complex machine options like automatic tool changers and handling robots.

Special feature: Program graphically with the POS 3000. Since ultimately, we know that: Your operating staff and preparation employees have a better eye for products than they do for IT programming lines. The machine, tool, work piece, and type of bend are all clearly displayed. That's why your employees bend visually on the screen beforehand and check the result in the software's 3D bending simulator, making sure that the sheet metal will be processed perfectly from the first bend. Bending programs that have already been created can be called up again quickly, checked visually, and corrected according to material requirements.



Above: the 3D display simplifi es dimensioning. Below: a 2D display of the bending position.

#### Working with POS 3000 is extremely comfortable:

Clearly laid-out product selection including a search function and navigation in submenus enables the operator to select work steps and connect them in the production plan menu to create sequences.

Individual product profiles can be designed very quickly via the intuitive finger-activated drawing feature. The exact dimensions may be entered and changed in the dimensioning menu. In order to check and coordinate together with the customer, the drawing may be output on paper using a printer.

Using the program that is created, the software generates the optimal sequence of bends, including automatic collision and threshold value monitoring. The folding angle and cut are corrected automatically using interpolation from the database.

#### Above: the position of the sheet on the back stop is displayed in the programming plan Below: POS 3000 simulates production in 3D.



#### Highlights

- 3D graphic control including a schematic depiction of the machine, tool, and work pieces
- Intuitive, visual touchscreen programming
- 3D bending simulator for visual program inspection
- Mount programming and control of the automatic tool changer
- Cycle time calculator
- Highspeed data transmission to frequency inverters (Ethernet Power Link)
- CAM connection, ERP/PPS interfaces, and DXF converter available

#### Option:

Unfold software "SCHRÖDER Unfold"

## Dimensions and technical data



EVO Center	3,200 x 4.0	4,000 x 3.0			
Working length (a)	3,240 mm	4,040 mm			
Sheet thickness (400 N/mm <sup>2</sup> )	4.0 mm	3.0 mm			
Machine length (b)	9,406 mm	10,206 mm			
Back gauge (c)					
U-1700	-	3,362 mm			
U- or rather J-3400	5,145 mm	-			
U- or rather J-4250	-	5,995 mm			
Weight with back gauge U-1700 (ca.)	14,000 kg	16,380 kg			
Clamping beam					
Geometry	180°	180°			
Stroke	850 mm	850 mm			
Drive power	2 x 6.69 kW	2 x 6.69 kW			
Speed	120 mm/s	120 mm/s			
Folding beam					
Adjustment, motorized	200 mm	200 mm			
Drive power	2 x 7.0 kW	2 x 7.0 kW			
Speed	150°/sec	150°/sec			
Folding center adjustment	80 m	m			

Bottom beam blade with finger grooves

\*Upon request the MAK 4 Evolution UD is also available in the working length 2,500 x 6.0 mm und 2,500 x 8.0 mm.



Dimension side table (wxd): NL 3200: 1,336 x 1,864 mm NL 4000: 1,716 x 2,614 mm

#### Dimension: EVO Center



Back gauge extension right and/or left with pneumatically lowerable gauge fi ngers (balls in table), combinable with side table:

Extension left 3400, 4 x 850 mm Extension left 4250, 5 x 850 mm Extension right 3400, 4 x 850 mm Extension right 4250, 5 x 850 mm



Standard: Gauge table 1700 mm in U-shape





## Schröder Group

The Schröder Group consists of Hans Schröder Maschinenbau GmbH, which is located in Wessobrunn, Germany, SCHRÖDER-FASTI Technologie GmbH, located in Wermelskirchen, Germany and the SMU GmbH, located in Leinburg-Weißenbrunn.

Founded in 1949, Hans Schröder Maschinenbau GmbH unifies traditional and modern approaches in machine building: Successfully managed as a quality and customer-oriented, family-owned company, Hans Schröder Maschinenbau is specialized in the development of modern machine concepts for bending and cutting sheet metal. The successful integration of the Fasti Company in 2006 and its worldwide presence make the Schröder Group one of today's leading providers of machines for bending, cutting, beading, flanging, and circular bending all types of sheet metal. The company's precision machines range from proven solutions for craftsmen to innovative, high-performance machines for automatic industrial production processes. 2021 the Schröder Group was expanded by the tool manufacturer SMU GmbH. Overall, the Schröder Group currently employs more than 300 people at various locations at home and abroad.

All information provided as a guide only and is subject to change at all times. HSM 230220EN

Hans Schröder Maschinenbau GmbH Feuchten 2 | 82405 Wessobrunn-Forst | Germany T +49 8809 9220-0 | F +49 8809 9220-700 E info@schroedergroup.eu www.schroedergroup.eu

