

SPECIAL OFFER

PowerBend Industrial UD

SCHRÖDER
GROUP

Take advantage of our special offer:
Renew your machinery and profit from a special price!

Motorized folding machine

PowerBend Industrial Up and Down

Now FOR FREE
3D technology package!



| Special offer | PowerBend Industrial | |
|---------------------------------------|---|----------|
| Working length | 3,200 mm | 4,000 mm |
| Sheet thckn. 400 N/mm ² | 6.0 mm | 5.0 mm |
| Software control | POS 3000 3D graphic control incl. remote maintenance and pc version | |
| Back gauge (3D technology package) | Positioning gauge as U-shape: 20 - 1600 mm, 2 sectors pneumatically lowerable, sheet support table with balls, recirculated ball screw, suction plates in gauge table with 4 suction units, program-controlled incl. positioning against the folding beam, 2 fixed square arms (left + right side), 2 pneumatic pop-up square arms assembled aisle side | |
| Clamping beam | Stroke 650 mm, geometry 180 °, drive 2 x 3.0 kW (converter-controlled, recirculated ball screws), hydraulic tool clamping, tool positioning display alongside the clamping beam | |
| Folding beam | Up'n Down folding beam, program-controlled; drive 2 x 5.5 kW (converter-controlled, trapezoidal sheet), hydraulic tool clamping, motorized folding beam adjustment 160 mm, motorized folding center adjustment +80/-15 mm, motorized central crowning device | |
| Others | Air conditioner | |
| Tools | Bottom beam blade one-piece 30° with finger grooves, minimal gauge 20 mm Folding blade 10 mm or 40 mm, ca. 1100 N/mm ² , surface-treated (phosphated) Goat's foot blade H = 300 mm, ca. 1100 N/mm ² , surface-treated ((phosphated) | |

++ Limited special offer until 31.12.2020 ++

Get your special price and break new grounds!

Schröder Group – your partner für quality and innovation!

Hans Schröder Maschinenbau GmbH

Feuchten 2 | 82405 Wessobrunn-Forst | Germany | T +49 8809 9220-0 | F +49 8809 9220-700

E info@schroedergroup.eu | www.schroedergroup.eu

All information provided as a guide and may be subject to change at any time.

